

TWIN FLUID PUMPING



15k 2000hp Twin

EQUIPMENT SPECS

- Two 800 HP Cat engines with quint 15k 3" fluid ends
- 400 HP auxiliary hydraulic engine
- Cat 6 speed transmissions with 2 speed auxiliary gear reduction
- 200 ft. of 2-inch 1502 line pipe on unit
- 120 ft. of 4-inch petroleum suction hoses with stainless steel locking camlocks
- Data recording system with ability to build charts and second by second data, that can be loaded onto a data stick for customer
- Ability to suck back own iron with a gear pump eliminating the need for a vac truck
- Built in chemical pumps
- 2-200G heated chemical storage totes built onto unit
- Built in electronic overpressure switches
- Manual PRV on fluid ends for backup

PUMPING SPECS

- Pumping Rates from as low as .5 BBL/min to 7.5 BBL/min at 7200 psi
- Pumping Rates as high as 15.7 BBL/min at 1500 psi
- Pumping Pressure from 0 psi to 15,000 psi
- Mixing Gel plugs on the fly in on-board mixing tanks
- Mixing KCL water

JOB SCOPES FOR UNIT

- High rate DFITS
- Packer inflation
- Coil Support
- Wireline pump downs
- Frac Support
- Stand alone pumping
- Mix and pumping weighted fluid for well control situations
- Acid Squeeze
- Injection Tests



**24 HOUR
DISPATCH
701.334.0167**

0.701.334.0167

EMAIL: pumping@fluidprousa.com

www.fluidprousa.com